[Lead2pass New 400-201 Exam Dump Free Updation Availabe In Lead2pass (561-580)

2017 November Cisco Official New Released 400-201 Dumps in Lead2pass.com! 100% Free Download! 100% Pass Guaranteed!
We at Lead2pass are committed to help you clear your 400-201 certification test with high scores. The chances of you failing to clear your 400-201 test, after going through our comprehensive exam dumps is very bleak. Following questions and answers are all new published by Cisco Official Exam Center: https://www.lead2pass.com/400-201.html QUESTION 561Which three network topologies can be deployed on the cisco ASR 9000 satellite nV System network? (Choose three) A. Mesh NetworkB. Layer 2 fabricC. Dual homeD. Overlay networkE. Dual ringF. Hub and spokeAnswer: BCF QUESTION 562Which two options are characteristics of MoFRR? (Choose two) A. Uses additional PIM join toward sourceB. Based on multicast forward error correction featureC. Based on PIM Fast RouteD. Requires MPLS TE FRR enabled with link protection and node protectionE. Utilizes two equal-cost paths toward source Answer: AE QUESTION 563Which two MVPN profile use either PIM or BGP-AD to advertise the Data-MDT? (Choose two) A. Profile 0 : Rosen GREB. Profile 5 : MS-PMSI (Partition) MLDP P2MP with BGP-ADC. Profile 3 : Rosen GRE with BGP-ADD. Profile 4 : MS-PMSI (Partition) MLDP P2MP with BGP-ADE. Profile 9 : Rosen MLDP with BGP-ADF. Profile 1 : Rosen MLDP Answer: CE QUESTION 564Refer to the exhibit. Customer Y reported that internet traffic stopped for a few minute. The ISP ABC operation engineer identified that this occurred when ASBR1 router reloaded OSPF coverage faster than BGP. Which command prevent this happening? A. Graceful restartB. set-overload-bit on startup wait-for-bgpC. bfd min_rx 100 max_rx 100 multiplier 3D. max-metric router-lsa on startup 300 Answer: D QUESTION 565Refer to the exhibit. Which PW type is negotiated? A. Type 1B. Type 2C. Type 3D. Type 4E. Type 5F. Type 6 Answer: E QUESTION 566Operations team must deploy Inter-Chassis Communication Protocol to provide high availability services to dual-homed CE nodes. On which nodes must the Inter-Chassis Communication Protocol be configured to meet this requirement? A. P nodesB. Metro Ethernet switches nodesC. CE nodesD. PE nodes Answer: D QUESTION 567A network engineer has a requirement to configure IP flow exporting using standard protocols on a cisco IOS XE device. Which configuration achieves this goal? A. flow exporter EXPORTERdestination 10.1.1.1export-protocol version 9transport udp 90B. flow exporter EXPORTERdestination 10.1.1.1source Loopback 0transport udp 90C. flow exporter EXPORTERdestination 10.1.1.1source Loopback 0transport udp 90version ipfixD. flow exporter EXPORTERdestination 10.1.1.1export-protocol ipfixtransport udp 90 Answer: D QUESTION 568Refer to the exhibit. A company has four office locations, which are identified as 1,2,3 and 4. The PE routers at these locations have assigned RDs of 10:10 , 20:20, 30:30 and 40:40, respectively Locations 1 and 3 need to share routing information. Which set of configurations allows for this requirement? A. Site 3:vrf defination ACMEroute-target import 10:20 route-target import 20:30route-target import 40:40B. Site 1:vrf defination ACMEroute-target import 15:15Site 3 :vrf deination ACMEroute-target import 15:15C. Site 1:vrf defination ACMEroute-target import 20:20route-target import 30:30route-target import 40:40D. Site 1:vrf definition ACMEroute-target export 15:15Site 3:vrf definition ACMEroute-target export 15:15E. Site 1:vrf definition ACMEroute-target import 30:30Site 3 :vrf definition ACMEroute-target import 10:10 Answer: E QUESTION 569 Drag and Drop QuestionDrag and drop the OSPF PE-CE components on the left onto correct description on the right Answer: QUESTION 570A customer requires to exchange BGP IPv6 prefixes with a service provider. However, the customer is unwilling to propagate its own IPv6 prefixes over the Internet through the service provider. What task engineer take to achieve this objective? A. Configure the IPv6 prefixes of the customer with the predefined BGP no-export community attributeB. Configure the BGP next-hop for IPv6 prefixes of the customer with the address of the ISP BGP route serverC. Define a route-map or RPL that blackholes all customer IPv6 prefixesD. Configure the IPv6 prefixes of the customer with the predefined BGP no-advertise community attribute Answer: A QUESTION 571Drag and Drop QuestionDrag and drop the characteristics of Cisco IOS and Cisco IOS XR from the left onto the correct kernel, memory management, and software packaging categories on the right Answer: QUESTION 572Which protocol provides fast link failure detection for all type of encapsulation? A. Prefix Independent ConvergenceB. Carrier delayC. Non stop forwardingD. Bidirectional forwarding detection Answer: D QUESTION 573Drag and Drop QuestionRefer to the exhibit. Drag and drop the NetConf architecture components from the left on to the correct network functionality on the right Answer: QUESTION 574The XYZ service provider network is composed of hundreds of routers that run OSPF and LDP. Which two LDP features can be used to increase peering update performance and reduce local memory consumption? (Choose two) A. Session protectionB. Specify label rangeC. AutoconfigD. Label allocation controlE. IGP syncF. Label acceptance control Answer: DF QUESTION 575Refer to the exhibit R1 is migrating from ISP 1 to ISP 2. The R1 ISO image does not support the 4-byte AS feature. Which configuration on R1 can establish this EBGP session? A. Router bgp 200Neighbor 10.10.24.4 local-as-65600B. Router bgp 200Neighbor 10.10.24.4 remote-as 23456C. Router bgp 200Neighbor

10.10.24.4 remote-as 65600D. Router bgp 200Neighbor 10.10.24.4 local-as-23456 Answer: B QUESTION 576Which three IS-IS TLVs floods the MPLS TE resource allocation information through the network? (Choose three) A. Traffic engineering router ID B. Extended IP reachabilityC. IS TE reachabilityD. RSVPE. Extended IS reachabilityF. Opaque Answer: ABE QUESTION 577Refer to the exhibit. AS 200 uses the CSC solution provided by AS 100 with regards to the packets originated on ABC-Site2 going toward to ABC-Site1, how many labels are in the label stack of these packets when they cross the link between CSC-PE2 and CS-P? A. 1B. 2C. 3D. 4 Answer: C QUESTION 578In an NFV environment, what is the role of an SDN controller? A. Dynamically controls all of the software componentsB. Spins up the VMs that are required to build the NFVsC. Dynamically scales up and scales down VM resourcesD. Connects the virtualized networking devices through a common policy-based model Answer: D QUESTION 579Which component does NSF rely on to ensure that interfaces remain up during switchover and that lower layer protocol state is maintained? A. SSOB. BFDC. IP FRRD. LFA Answer: A QUESTION 580 Which description is true of what the fast-reroute keep-all-paths command accomplishes when under OSPF process? A. Besides the regular LFA backup paths, this command also installs the remote LFA backup pathsB. By default, only the/32 routes have a backup path installed. This command creates a backup path for the router with any subnet maskC. All backup routes-not only the best backup route-are installed in the OSPF RIBD. All possible alternate routes are installed in the OSPF RIB, even if the alternate paths do not meet LFA criteria (the LFA inequalities) Answer: C Lead2pass helps millions of candidates pass the Cisco 400-201 exam and get the certification. We have tens of thousands of successful stories. Our dumps are reliable, affordable, updated and of really best quality to overcome the difficulties of Cisco 400-201 certifications. Lead2pass exam dumps are latest updated in highly outclass manner on regular basis and material is released periodically. 400-201 new questions on Google Drive: https://drive.google.com/open?id=0B3Syig5i8gpDMExNMWJIYTlIcUU 2017 Cisco 400-201 exam dumps (All 647 Q&As) from Lead2pass: https://www.lead2pass.com/400-201.html [100% Exam Pass Guaranteed]